

HV, K Series Hand Switching Valve



We make the difference

- Valve
- DJF
- JELMP
- JELP/G
- MCS
- 4V100
- 4V200
- 4V300
- 4V400
- Manifold
- SV
- 3V1
- JEL
- 3VJZF
- 4VJZF
- MVSD
- VF, VZ
- BM
- Diaphragm
- Coil
- 2V
- 2W
- 2W(Big)
- 2P
- 2L
- VX
- PU
- PU225
- 2Q
- JEL5404
- JEL6213
- BU
- Pulse
- JELJZF
- 4H
- TSV
- MPV
- 4HV
- HV, K**
- 4R
- FV
- MSV
- JM
- ASC, RE
- QE, QEA
- ST
- HSV



K34R₈-L8

HV400

HV400

Ordering Code

HV	400	02	B	K	34	R₈	L8
Specification	Series	Port Size	Connection type	Specification	Series	Port Size	Connection Type
Hand Switching Valve		02: G 1/4" 03: G 3/8" 04: G 1/2"	Blank: Threaded B: Sub-plated	Hand Switching Valve	24: 4/2 Way 34: 4/3 Way	R ₈ : Hand Switching Valve	L6: G 1/8" L8: G 1/4"

Specification

Model	HV400-02	HV400-03	HV400-04	K34R ₈ -L6	K34R ₈ -L8
Working Medium	40 Micron Filtered Air				
Port Size	G 1/4"	G 3/8"	G 1/2"	G 1/8"	G 1/4"
Effective Cross Section Area	30 mm ² (CV=1.68)			18 mm ² (CV=1.00)	
Working Pressure	0 ~ 0.8 MPa				
Max. Ambient Temperature	0 ~ 60 °C				

Overall Dimension

